



WAFER (SERRATED FACE)

ITEM N°	PART
1	WAFER
2	CLAPPER
3	HINGE PIN
4	PIN RETAINER
5	SEAL ("O" RING)
6	EYE BOLT <sup>3</sup> / <sub>4</sub> " HEX. NUT

NOTES

- VITON O RING INSERT IN WAFER IS STANDARD. TEFLON OR BUNA N NITRAL O RING OR METAL TO METAL CAN BE FURNISHED.
- INSERT CAN BE PLACED ON CLAPPER UPON REQUEST
- STAINLESS TRIM FURNISHED IF SPECIFIED.
- O RING DIMENSIONS ARE I.D.
- FACE FINISHED RAISED UNLESS A FLAT DIMENSION IS REQUESTED.
- ALL CORNERS HAVE 1/16" CHAMFER.



FLANGE FACE ALTERNATES

DIMENSIONS IN VALVE SIZE																	
	2"	2 1/2"	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	24"	30"	36"	42"	48"
A	4 5/8	5 1/8	5 7/8	7 1/8	9 7/8	12 1/8	14 1/4	16 7/8	19 1/8	21 1/4	23 1/2	25 3/4	30 1/2	37 1/2	44	50 3/4	00
B	1 1/8	1 3/8	1 3/4	2 5/8	4 5/8	6	7 3/4	9 1/2	10 1/2	12 1/2	14	16	19 1/4	24	28 3/4	33 1/2	00
C	3/4	3/4	3/4	3/4	1	1 1/8	1 1/2	2	2 1/4	2 3/4	3	3 1/4	3 3/4	4 3/4	5 1/4	6	00

CONTACT FACTORY FOR 00 DIMENSIONS

Part #

**Champion Short Pattern Reduced Port Wafer Check Valve**



P.O. Box 333  
 CYPRESS, TX 77410

WAFER CHECK VALVE  
 ANSI 300 LB. 2" thru 42"