



WAFER (SERRATED FACE)

ITEM N°	PART
1	WAFER
2	CLAPPER
3	HINGE PIN
4	PIN RETAINER
5	SEAL ("O" RING)
6	EYE BOLT ³ / ₈ HEX. NUT

NOTES

1. VITON O RING INSERT IN WAFER IS STANDARD. TEFLON OR BUNA N NITRAL O RING OR METAL TO METAL CAN BE FURNISHED.
2. INSERT CAN BE PLACED ON CLAPPER UPON REQUEST
3. STAINLESS TRIM FURNISHED IF SPECIFIED.
4. O RING DIMENSIONS ARE I.D.
5. FACE FINISHED RAISED UNLESS A FLAT DIMENSION IS REQUESTED.
6. ALL CORNERS HAVE 1/16" CHAMFER.



R.T.J. FLANGE FACE
 AVAILABLE FOR 900 LB.
 "B" DIM. INCREASED 1/2"
 FLANGE FACE ALTERNATES

DIMENSIONS IN VALVE SIZE																
	2"	2 1/2"	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	24"	26"	30"	36"
A	4 3/8	5 1/8	5 7/8	7 5/8	10 1/2	12 5/8	15 3/4	18	19 3/8	22 1/4	24 1/8	26 7/8	31 1/8	34 1/8	38 1/4	44 1/2
B	1	1 3/8	1 3/4	2 5/8	4	5	6 7/8	8 1/2	9 1/2	11	12 1/2	14 1/4	17 3/8	19	22	26 1/2
C	3/4	3/4	3/4	7/8	1 1/8	1 1/2	2 1/4	2 3/8	2 3/8	2 7/8	3 1/8	3 5/8	4 1/4	4 3/4	5 1/4	6 1/4

Part #

Champion Short Pattern Reduced Port Wafer Check Valve



P.O. Box 333
 CYPRESS, TX 77429

WAFER CHECK VALVE
 ANSI 600 LB. 2" thru 36"