



WAFER (SERRATED FACE)

| ITEM N° | PART |
|---------|-----------------------------------------------|
| 1 | WAFER |
| 2 | CLAPPER |
| 3 | HINGE PIN |
| 4 | PIN RETAINER |
| 5 | SEAL ("O" RING) |
| 6 | EYE BOLT ³ / ₈ HEX. NUT |

NOTES

1. VITON O RING INSERT IN WAFER IS STANDARD. TEFLON OR BUNA N NITRAL O RING OR METAL TO METAL CAN BE FURNISHED.
2. INSERT CAN BE PLACED ON CLAPPER UPON REQUEST
3. STAINLESS TRIM FURNISHED IF SPECIFIED.
4. O RING DIMENSIONS ARE I.D.
5. FACE FINISHED RAISED UNLESS A FLAT DIMENSION IS REQUESTED.
6. ALL CORNERS HAVE 1/16" CHAMFER.



FLANGE FACE ALTERNATES

| DIMENSIONS IN VALVE SIZE | | | | | | | | | | | | | | | | |
|--------------------------|-------|--------|-------|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| | 2" | 2 1/2" | 3" | 4" | 6" | 8" | 10" | 12" | 14" | 16" | 18" | 20" | 22" | 26" | 30" | 36" |
| A | 5 5/8 | 6 1/2 | 6 5/8 | 8 1/8 | 11 1/8 | 14 1/8 | 17 1/8 | 19 5/8 | 20 1/2 | 22 5/8 | 25 1/8 | 27 1/2 | 33 | 34 3/4 | 39 3/4 | 47 1/4 |
| B | 1 | 1 3/8 | 1 3/4 | 2 5/8 | 4 | 5 | 6 7/8 | 8 1/2 | 9 1/2 | 11 | 12 1/2 | 14 1/4 | 17 3/8 | 19 | 22 | 26 1/2 |
| C | 3/4 | 3/4 | 7/8 | 7/8 | 1 3/8 | 1 3/4 | 2 1/4 | 2 3/4 | 2 3/4 | 3 1/4 | 3 3/4 | 4 1/4 | 5 1/4 | 5 3/4 | 6 3/4 | 8 1/4 |

Part #

Champion Short Pattern Reduced Port Wafer Check Valve



P.O. Box 333
 Cypress, TX 77410

Wafer Check Valve
 ANSI 900 LB. 2" thru 36"